

HOT ROLLED STEEL ROUND BAR GRADE SCM440

Size (mm)	Diameter Tolerance		Weight (kg)/ 1 m.
	-	+	
16.00	0.50	0.50	1.58
19.00	0.50	0.50	2.23
22.00	0.50	0.50	2.99
25.00	0.50	0.50	3.85
26.00	0.50	0.50	4.17
28.00	0.50	0.50	4.84
30.00	0.50	0.50	5.55
32.00	0.50	0.50	6.32
36.00	0.50	0.50	7.99
38.00	0.50	0.50	8.91
50.00	0.50	0.50	15.42
55.00	0.50	0.50	18.66
60.00	0.70	0.70	22.20
65.00	0.70	0.70	26.06
75.00	0.70	0.70	34.69
80.00	0.70	0.70	39.47
90.00	1.00	1.00	49.96
100.00	1.00	1.00	61.68
105.00	1.30	1.30	68.00
115.00	1.30	1.30	81.57
120.00	1.30	1.30	88.82
130.00	1.30	1.30	104.24
140.00	1.30	1.30	120.89
150.00	1.30	1.30	138.78
160.00	1.50	1.50	157.90

HOT ROLLED STEEL ROUND BAR GRADE SCM440

Size (mm)	Diameter Tolerance		Weight (kg)/ 1 m.
	-	+	
170.00	1.50	1.50	178.25
180.00	1.50	1.50	199.84
190.00	1.50	1.50	222.66
200.00	2.50	2.50	246.71
210.00	2.50	2.50	272.00
220.00	2.50	2.50	298.52
230.00	2.50	2.50	326.28
240.00	2.50	2.50	355.27
250.00	3.00	3.00	385.49
260.00	3.00	3.00	416.95
270.00	3.00	3.00	449.64
280.00	3.00	3.00	483.56
290.00	3.00	3.00	518.72
300.00	3.00	3.00	555.11
310.00	3.00	3.00	592.73

หมายเหตุ

คำนวณน.พลาทม=ค่า(mm.)*ค่า(mm.)*ความยาว(mm.)/162131